

RG-EG710XS

Reyee 10-Port High-Performance Cloud Managed Router for Up to 700 Clients



Highlights

- High capacity supporting up to 700 concurrent clients.
- 3 Gbps throughput, high-performance router for office networks.
- Powerful VPN with 300 tunnels for branches and remote employees.
- Efficient bandwidth management based on applications and users.
- Multi-WAN, intelligent load balancing.
- Lifetime management on Ruijie Cloud anytime, anywhere.

Highlight Features

Unleashing Speed, Empowering Connections

High-Speed Business Router for Up to 700 Clients

RG-EG710XS



700
Concurrent Clients



300
VPN Tunnels



3 Gbps
Throughput




Multi-WAN
Load Balancing

Speed. Security. Power.


RG-EG710XS Can Fit Diverse Networking Scenarios with Ease

Scenarios


Concurrent Clients



Offices



HQ with Multi-Branches



Hotels



Authentication
and Authorization



VPN
IPsec, OpenVPN,
L2TP, PPTP, WireGuard



Customized
Portal Page

Speed. Security. Power.

RG-EG710XS Can Fit Diverse Networking Scenarios with Ease

Scenarios

Concurrent Clients




Connect Up to **700** Clients


Highlight Features

Easy NAT Traversal

The management console uniformly displays all third-party devices, enabling easy intranet access and one-click links to their web interfaces.



Client Recognition & Flow Control



Cloud, Make Your Business Easy

- Self-organizing network
- Scenario-based configuration guide
- Marketing portal authentication
- Quickly advanced service setup by APP
- Remote management based on Ruijie Cloud and Ruijie Reycap App



Hardware Specifications

Model	RG-EG710XS
System Specifications	
CPU	Quad-core processor, 1.8 GHz clock frequency per core
Flash memory	256 MB
RAM	2 GB
Port Specifications	
Total number of optical ports	2
Total number of RJ45 ports	8
Number of 10/100/1000BASE-T ports	4
Number of 10/100/1000/2500BASE-T ports	4
Number of 10GE SFP+ ports	2
Maximum number of LAN ports	9
Maximum number of WAN ports	9
Number of fixed LAN ports	1
Number of fixed WAN ports	1
Number of LAN/WAN ports	8
LEDs	1 x system status LED 10 x Ethernet port LEDs
Reset button	1
Environment and Reliability	
Cooling	Natural cooling
Fan	Fanless design

/ Hardware Specifications

Model	RG-EG710XS
Mounting options	Rack Note: The device occupies 1 U of the rack space.
Operating humidity	10% RH to 90% RH (non-condensing)
Operating temperature	0°C to 40°C (32°F to 104°F)
Storage humidity	5% RH to 95% RH (non-condensing)
Storage temperature	–40°C to +70°C (–40°F to +158°F)
Surge protection	Service port: ±6 kV for common mode Power connector: ±6 kV for common mode and ±6 kV for differential mode
Dimensions and Weight	
Package dimensions (W x D x H)	605 mm x 480 mm x 315 mm (23.82 in. x 18.9 in. x 12.4 in.)
Product dimensions (W x D x H)	440 mm x 210 mm x 43.6 mm (17.32 in. x 8.27 in. x 1.72 in.)
Shipping weight	3.5 kg (7.72 lbs)
Weight	2.65 kg (5.84 lbs)
Power Supply and Consumption	
Power supply	Fixed power supply
Maximum power consumption	14 W

Software Specifications

Model	RG-EG710XS
System Performance Capacity	
Maximum number of concurrent sessions	150000
Recommended number of concurrent clients	700
Throughput	4000 Mbps (Turbo Mode)
	3000 Mbps (Normal Mode)
IP Service	
3322.org	Yes
ALG	Yes
ARP binding	Yes
Maximum number of ARP entries	2048
Proxy ARP	No
Cloudflare	Yes
DHCP client	Yes
DHCP server	Yes
DHCP relay	No
Option 43	Yes
Option 138	Yes
Static/Dynamic NAT	Yes
NAT-PT	No

Software Specifications

Model	RG-EG710XS
Turbo mode	yes
NAT loopback	Yes
DNS client	Yes
DNS proxy	Yes
DNS server	Yes
DNS blocklist or allowlist	Yes
Maximum number of domains supported by a DNS blocklist or allowlist	2000
Maximum number of policies supported by a DNS blocklist or allowlist	10
No-IP DNS	Yes
GRE tunnel	No
IPTV	Yes
IPv4 ping	Yes
IPv6	Yes
IPv6 ping	Yes
Number of port mapping entries	512
Port mapping	Yes
DDNS	Yes

Software Specifications

Model	RG-EG710XS
Ruijie DDNS	Yes
Alibaba Cloud DDNS	Yes
UPnP	Yes
Number of sub-interfaces configured on a WAN port	32
VPN	
IPsec VPN	Yes
IPsec VPN bandwidth	1100 Mbps
Maximum number of branches in IPsec VPN networking	300
L2TP VPN	Yes
L2TP VPN bandwidth	1100 Mbps
Maximum number of branches in L2TP VPN networking	300
OpenVPN	Yes
OpenVPN bandwidth	350 Mbps
Maximum number of branches in OpenVPN networking	300
PPTP VPN	Yes
PPTP VPN bandwidth	1700 Mbps

Software Specifications

Model	RG-EG710XS
Maximum number of branches in PPTP VPN networking	300
SSL VPN	No
Easy VPN 1.0	No
Number of VPN accounts for L2TP, PPTP, and OpenVPN	700
WireGuard server	Yes
WireGuard client	Yes
WireGuard performance	1100 Mbps
Number of concurrent tunnels supported by the WireGuard server	300
Reliability	
Stacking	No
VRRP	No
Network Management and Monitoring	
Web management	Yes
Ruijie Cloud management	Yes
Management on Ruijie Reyee App	Yes
Remotely monitoring devices through Ruijie Reyee App	Yes

Software Specifications

Model	RG-EG710XS
Restarting devices through Ruijie Reyee App	Yes
Upgrading device software version through Ruijie Reyee App	Yes
Fault diagnosis	Yes
FTP client (IPv4 address)	No
FTP server (IPv4 address)	No
TFTP client (IPv4 address)	Yes
TFTP server (IPv4 address)	No
HTTPS login	Yes
NTP client	Yes
NTP server	No
Scheduled device restart	Yes
SNMPv1, v2c, and v3	Yes
SON	Yes
SSH	No
Telnet	No
Web login information	Default IP Address: 192.168.110.1 Default Password: admin
Maximum number of managed devices (router mode)	AP and NBS series: 750 ES series: 128

Software Specifications

Model	RG-EG710XS
	Note: The maximum number of managed devices varies with each device series.
Maximum number of managed devices (AC mode)	AP and NBS series: 750 ES series: 128 Note: The maximum number of managed devices varies with each device series.
SD-WAN	
SD-WAN	Yes
SD-WAN performance	1100 Mbps
Number of tunnels supported by SD-WAN	1500
Maximum number of SD-WAN branches	300
Active/Standby mode (automatically switching to the standby interface when the active interface fails)	Yes
Tunnel bandwidth test	Yes
Bypass networking for a device in AP mode	No
Centralized traffic forwarding policy	Yes

Software Specifications

Model	RG-EG710XS
Multi-WAN bandwidth aggregation efficiency (lab data)	$\geq 80\%$
Ethernet Switching	
Link aggregation	No
LLDP	No
VLAN	Yes
Maximum number of VLANs	128
VLAN configuration supported on LAN ports	Yes
Super-VLAN	No
Configuring the same VLAN tag for multiple WAN ports	Yes
VLAN priority	Yes
Number of MAC address entries to be filtered	512
Authentication	
Portal authentication	Yes
One-click authentication	Yes
Password authentication	Yes
SMS-based authentication	Yes

Software Specifications

Model	RG-EG710XS
Voucher authentication supported by Ruijie Cloud portal page	Yes
Cloud portal authentication	Yes
Local portal authentication	Yes
QR code authentication	Yes
Custom portal page	Yes
Account-based authentication supported by Ruijie Cloud portal page	Yes
CHAP, MS-CHAPv1, MS-CHAPv2	Yes
Delivery through Ruijie Cloud portal page	Yes
802.1X authentication	Yes
MAC address-based authentication	Yes
PPPoE server	Yes
Number of accounts supported by the PPPoE server	700
RADIUS flow control authorization supported by WISPr authentication	Yes
Number of concurrent clients supported by the PPPoE server	500

Software Specifications

Model	RG-EG710XS
RADIUS flow control authorization supported by PPPoE authentication	Yes
PAP	Yes
RADIUS authentication	Yes
RADIUS client	Yes
RADIUS accounting based on time or traffic	Yes
RADIUS proxy server	Yes
RADIUS traffic quota authorization	Yes
RADIUS user group authorization	Yes
Third-party authentication	Yes
Security	
ACL	Yes
IPv6 ACL	Yes
DHCP snooping	No
Malformed packet attack defense	Yes
Fragmentation attack defense	Yes
Teardrop attack defense	Yes
LAND attack defense	Yes
SYN flood attack defense	Yes
Smurf attack defense	Yes

Software Specifications

Model	RG-EG710XS
IP attack defense	Yes
Disabling ping	Yes
Stateful ACL	Yes
IP-MAC binding	Yes
Network sharing prevention	Yes
Security log	Yes
Security zone	Yes
User group-based connection limiting	Yes
Ethernet Interface	
Avoiding IP address conflicts on WAN interfaces	Yes
Multiple IP addresses on a WAN port	Yes
Sub-interface	Yes
Load balancing	Yes
MAC address cloning	Yes
Multiple WAN interfaces on the same network segment	Yes
PPPoE clients	Yes
Scheduled PPPoE reconnection	No
Basic Configurations	

Software Specifications

Model	RG-EG710XS
AC mode	Yes
Automatically identifying the Internet access mode and obtaining IP addresses	Yes
Automatically learning the PPPoE username and password of other routers	Yes
Configuration backup	Yes
Internet access mode	Static IP address Static IPv6 address Dynamic IP address Dynamic IPv6 address PPPoE
Local upgrade	Yes
Log upload	Yes
Online upgrade	Yes
Restoring factory defaults	Yes
System language	English, Chinese, Turkish, Arabic, Vietnamese, Thai, Indonesian, Latin American Spanish, Brazilian Portuguese, Russian, French, German, European Spanish, Italian, and Polish
IP Routing	

Software Specifications

Model	RG-EG710XS
Application-based routing	Yes
Bandwidth aggregation	Yes
BGP	Yes
BGP4	Yes
BGP4+	Yes
ECMP	No
IPv4 static route	Yes
IPv6 PBR	Yes
Route selection based on national address database	Yes
IPv6 static route	Yes
IS-ISv4	No
IS-ISv6	No
Load balancing based on flows	Yes
Load balancing based on source IP addresses	Yes
Load balancing based on the interface weight	Yes
Route selection by link quality	Yes
OSPFv2	Yes
OSPFv3	Yes

Software Specifications

Model	RG-EG710XS
RIP	Yes
RIPng	Yes
Gateway Features	
WAN failover	Yes
Application priority	Yes
Application recognition	Yes
Behavior management	Yes
QoS	Yes
Time-based blocking policy	Yes
IP address-based blocking policy	
Website filtering: custom URL	Yes
Traffic audit	Yes
URL audit log	Yes
Audit log server	Yes
Audit log storage	Yes
Uploading audit logs to a server	Yes
WLAN	
Wireless Intelligent Optimization (WIO)	Yes
MPLS	
MPLS L2VPN	No

Package Contents

Model	RG-EG710XS
Manual	
User Manual	1
Warranty Card	1
Accessories	
Rack-mount bracket	2
Power cord	1 x 1.8 m (70.86 in.)
Power cord retention clip	1
Rubber pad	4
Screw	8 x M4 x 8 mm cross recessed countersunk head screws

Ruijie | ReYee

 **R**edefine **y**our **e**asy network



Ruijie Networks Co., Ltd.

Official Website: <https://Reyee.Ruijie.com>